


## AGRITEC BANDSAW 6

**Product Code:** AGR001 | **Revision:** 20240819



Mineral oil based neat cutting fluid for sawmills.

### Available Pack Sizes



### Applications

Based on high quality solvent refined mineral oil and designed for proactive sawmills to improve the reliability of the blades. Carefully formulated to make the cutting process smoother, comply with Health and Safety requirements and to improve the work piece visibility.

### Benefits

- Excellent anti-wear properties.
- Improves finish quality.
- Prevents corrosion.
- Reduces pitch build-up on blades.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.84
Flash Point (°C)	ASTM D92	>130
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	6
Pour Point (°C)	ASTM D97	-15

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the equipment's maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to the elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.