

AGRITEC CHAINSAW 220XT

Product Code: AGR006 | **Revision:** 20241121



Premium anti-fling chainsaw oil.

Available Pack Sizes



Applications

A tenacious and tacky lubricant developed for the lubrication of chainsaw guide bars, sprockets and chains. Incorporating advanced surface active agents to ensure maximum penetration of the chain to reduce wear, provide corrosion protection and resist the tendency to fling during operation.

Recommended by Aztec Oils as suitable for the following applications

ISO 6743-1 L-AC

Primarily for the lubrication of guide bars, sprockets and chains of pressure-fed chainsaws requiring an ISO 220 or SAE 50 lubricant.

Benefits

- Advanced extreme pressure anti-wear additive technology.
- Anti-fling tackiness agents resist oil fling.
- Protects from rust & corrosion.
- Wide temperature range, suitable for use throughout all seasons.
- Suitable to use in applications requiring an ISO 220 or SAE 50 chainsaw lubricant.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.90
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	220
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	19.5
Pour Point (°C)	ASTM D97	-10
Viscosity Index	ASTM D2207	101

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.