


AGRITEC SUTO 10W-40 SS

Product Code: AGR012 | **Revision:** 20250722



High-performance semi-synthetic super universal tractor oil.

Available Pack Sizes



Applications

A premium-quality super universal tractor oil manufactured from a blend of select mineral and synthetic base oils combined with specialised additive technology. Suitable for use in four-stroke petrol and diesel engines, hydraulic systems and transmissions, including equipment with oil-immersed wet brakes. Featuring a very low pour point and a high viscosity index, it ensures minimal wear during cold starts while maintaining an effective lubrication film at elevated temperatures. This high-performance universal oil is engineered to deliver reliable protection and performance under severe operating conditions.

Performance Levels

ACEA E3
API (Engine) SF/CG-4
API (Transmission) GL-4
Allison C4
Case MS 1204/1206
Case New Holland MAT 3525
Caterpillar TO-2
Ford M2C86-C, M2C134-D
John Deere J20C
MAN 271
Massey Ferguson M1139, M1143, M1144, M1145
Mercedes-Benz 228.1
ZF TE-ML 06B, 06C, 07B, 07D

Benefits

- Good anti-foaming and air release properties.
- Helps reduce wet brake squawk & chatter.
- Provides excellent anti-wear protection.
- Engineered to have good oxidation resistance, thermal stability and superb low temperature performance.
- Suitable for most agricultural machinery.
- Natural high lubricity.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.87
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	95.5
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	13.8
Pour Point (°C)	ASTM D97	-35
Viscosity Index	ASTM D2207	148

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the equipment's maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.