

AGRITEC MILKING MACHINE OIL

Product Code: AGR016 | **Revision:** 20241031



Mineral based ashless lubricant for milking machines.

Available Pack Sizes



Applications

Manufactured from a blend of premium quality paraffinic base oils and high performance ashless additive technology for superb levels of protection from wear, rust and oxidation. Its rapid water separation ability ensures that the lubricant cleanly separates in the presence of moisture or condensation. Designed to minimise deposit formation with excellent resistance to foaming and air release properties to ensure a long service life.

Recommended by Aztec Oils as suitable for the following applications

ISO VG 68

Suitable for use in a variety of vacuum pumps operating within the dairy industry, including Alfa Laval, Fullwood & Westfield milking machines.

Benefits

- Demulsifying to ensure rapid water separation.
- Good anti-foam & air release properties.
- Good low temperature flow characteristics allow for easy cold starting.
- Outstanding corrosion protection.
- Superior oxidation & thermal resistance for long-lasting trouble free operation.

Typical Test Data

Appearance		Straw/amber, undyed
Density @ 15°C (kg/m ³)	ASTM D4052	0.87
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	68
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	8.8
Pour Point (°C)	ASTM D97	<-25
Viscosity Index	ASTM D2207	102

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.