





# **AGRITEC BIO CHAINSAW 68**

Product Code: AGR017 | Revision: 20220322



Environmentally friendly anti-fling chainsaw lubricant.

#### **Available Pack Sizes**









### **Applications**

Specially formulated biodegradable chainsaw oil manufactured from naturally occurring esters which has been developed for the lubrication of chainsaw cutter bars. Incorporates advanced surface active agents to ensure maximum penetration of the chain to reduce wear, provide corrosion protection and resist the tendency to fling-off during operation.

Recommended by Aztec Oils as suitable for the following applications

Primarily for the lubrication of cutter bars and chains of pump & pressure-fed chainsaws requiring an ISO 68 or SAE 20 lubricant.

#### **Benefits**

- · Advanced EP & tackiness properties.
- Improves chain life.
- Protects against corrosion.
- Readily biodegradable & environmentally friendly.
- Resistant against oil fling.
- Naturally high viscosity index.

Typical Test Data		
Density @ 15°C (kg/m3)	ASTM D4052	0.92
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm/s²)	ASTM D445	68
Kinematic Viscosity @ 100°C (mm/s²)	ASTM D445	14.6
Pour Point (°C)	ASTM D97	<-10
Viscosity Index	ASTM D2207	226

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

## Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.