


AGRITEC UTTO SS HD

Product Code: AGR022 | **Revision:** 20250812



10W-40 semi synthetic universal tractor transmission oil.

Available Pack Sizes



Applications

A premium semi synthetic universal transmission and hydraulic fluid, specifically designed for use in agricultural and plant transmissions, hydraulics and rear axles including oil immersed wet brakes. Using a blend of high quality base oils and exceptional additive technology to provide an advanced lubricant which demonstrates excellent performance characteristics against various stringent test requirements of major equipment manufacturers'.

Recommended by Aztec Oils as suitable for the following applications

API GL-4
Allison C4
Case MS 1210
Caterpillar TO-2
Ford M2C86-B/C, M2C134-D
John Deere J20C
Massey Ferguson M1143, M1145
ZF TE-ML 03E, 05F, 06K, 17E, 21F

Benefits

- Allows for rationalisation of products.
- Good resistance against aeration & foaming.
- Engineered to have good oxidation resistance, thermal stability.
- Excellent brake squawk and chatter suppression.
- Exceptional anti-wear properties.
- Provides constant frictional performance.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.87
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	95
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	13.5
Pour Point (°C)	ASTM D97	-36
SAE Viscosity		10W-40
Viscosity Index	ASTM D2207	143

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the equipment's maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.