

AGRITEC TWO STROKE

Product Code: AGR037 | **Revision:** 20240819



Mineral based two stroke oil for horticultural equipment.

Available Pack Sizes



Applications

High quality mineral oil based two stroke engine oil which is blended with added performance additive technology for a reduced smoke, clean burning lubricant which reduces the need for maintenance. Suitable for use in all two stroke engines found in horticultural or plant equipment, including lawn mowers, chainsaws, hedge trimmers, brush cutters and other two stroke machinery. It is suitable for use in pre-mix and oil injection systems.

Recommended by Aztec Oils as suitable for the following applications

API TC
JASO FB
ISO-L-EGB
Suitable for use in agricultural & horticultural machinery, including chainsaws, hedge cutters, strimmers, brush cutters, etc.

Consult the manufactures handbook for instructions on mixing and dilution ratios.

Benefits

- Excellent deposit & wear control.
- Low ash for reduced deposit formation.
- Protects against piston & cylinder scuffing.
- Readily miscible in petrol.
- Reduced smoke formulation.

Typical Test Data

Appearance		Red
Density @ 15°C (kg/m ³)	ASTM D4052	0.879
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	58
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	8.2
Pour Point (°C)	ASTM D97	<-20
Sulphated Ash (%)	ASTM D874	0.6
Total Base Number (mg KOH/g)	ASTM D2896	0.6
Viscosity Index	ASTM D2207	110

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.