

AGRITEC SS TWO STROKE

Product Code: AGR038 | **Revision:** 20250813



Universal semi synthetic 2-stroke oil, ideal for horticultural & agricultural applications.

Available Pack Sizes



1L



5L

Applications

High performance semi synthetic two stroke engine oil specially manufactured from a blend of high quality base oils with added performance additive technology for a low smoke, clean burning lubricant which reduces the need for maintenance. Suitable for use in all two stroke engines found in horticultural or plant equipment, including lawn mowers, chainsaws, hedge trimmers, brush cutters and other two stroke machinery. It is suitable for use in pre-mix and oil injection systems.

Recommended by Aztec Oils as suitable for the following applications

API TC
JASO FC
ISO-L-EGC
Suitable for use in agricultural & horticultural machinery, including chainsaws, hedge cutters, strimmers, brush cutters, etc.

Consult the manufactures handbook for instructions on mixing & dilution ratios.

Benefits

- Excellent deposit & wear control.
- Improved system cleanliness.
- Low ash for reduced deposit formation.
- Low smoke formulation.
- Protects against piston & cylinder scuffing.
- Promotes easier starting.
- Readily miscible in petrol.

Typical Test Data

Appearance		Clear & bright, red
Density @ 15°C (kg/m ³)	ASTM D4052	0.88
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	90
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	11.1
Sulphated Ash (%)	ASTM D874	<0.25
Total Base Number (mg KOH/g)	ASTM D2896	0.7
Viscosity Index	ASTM D2207	110

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.