





# **NUTRITEC SYN MF 150**

**Product Code:** AZF015 | **Revision:** 20250310



NSF H1 Food grade synthetic PAO multifunctional lubricant.

#### **Available Pack Sizes**







#### **Applications**

A multifunctional synthetic lubricant formulated for use in the food industry where there is the possibility of incidental food contact. Designed for use in the food, drink, packaging and poultry industries in applications requiring the additional performance benefits of polyalphaolefin (PAO) base stocks. Designed for the lubrication of food machinery with the possibility of incidental food contact. This includes circulating and hydraulic systems, enclosed gears, closed heat transfer systems, joints, spindles, motors, actuators, spiral freezer chains, vacuum pumps and compressors. It is also suitable for other applications where a clean, colourless, non-staining fluid is desired.

Recommended by Aztec Oils as suitable for the following applications

DIN 51517 Part III DIN 51524 Part III HVLP ISO 12925-1 CKD US Steel 224 Halal & Kosher certified NSF H1 Ref 151465

#### **Benefits**


- Excellent anti-wear characteristics.
- · Extended oil life.
- Outstanding corrosion protection.
- Suitable to use in multiple applications to allow rationalisation and reduce the risk of misapplication.
- · Superb resistance to oxidation.
- Wide range of viscosities available to suit all requirements.

Typical Test Data		
Appearance		Clear liquid
Density @ 15°C (kg/m³)	ASTM D4052	0.83
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm²/s)	ASTM D445	150
Kinematic Viscosity @ 100°C (mm²/s)	ASTM D445	21
Pour Point (°C)	ASTM D97	<-40
Viscosity Index	ASTM D2207	164

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

## Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.







### Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- Providing that the product has been stored correctly, we recommend using the product within 5 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.