





CLASSIC LD 20W-50

Product Code: CLA001 | **Revision:** 20240820



Premium classic multigrade engine oil for vehicles from the 60's, 70's & 80's.

Available Pack Sizes







Applications

This multigrade engine oil is particularly suited to vehicles from the 1960's through to the 1980's where a detergent/dispersant lubricant is required for engines with filtration systems. The oil is designed to suspend and carry deposits back to the oil filter, preventing these deposits from circulating around the engine. Suitable for use in all seasons, saving the need to change between winter and summer grade engine oils.

Performance Levels

API SE/CC CCMC D1, G1 US MIL-L 2104B

Suitable for use in Classic Mini engines.

Benefits

- Advanced anti-wear technology helps to protect engine components.
- High shear stability for stay in grade performance.
- · High viscosity helps to reduce oil loss and leakage.
- Modern additive technology for vehicles equipped with filtration systems.
- Reduces corrosion, varnish and the agglomeration of sludge.
- Reliable cold starting.

Typical Test Data		
Density @ 15°C (kg/m³)	ASTM D4052	0.880
Flash Point (°C)	ASTM D92	219
Kinematic Viscosity @ 40°C (mm²/s)	ASTM D445	145
Kinematic Viscosity @ 100°C (mm²/s)	ASTM D445	17.8
Pour Point (°C)	ASTM D97	-30
Total Base Number (mg KOH/g)	ASTM D2896	7
Viscosity Index	ASTM D2207	136
ZDDP Concentration (Average)		900ppm

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.







Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.