

CLASSIC SPRINT 20W-50

Product Code: CLA012 | **Revision:** 20240820



High-performance semi synthetic based classic engine oil fortified with an advanced ZDDP anti-wear package.

Available Pack Sizes



Applications

Multigrade semi synthetic engine oil specially engineered for classic and high-performance vehicles. Formulated with high levels of zinc and phosphorous for exceptional levels of anti-wear protection on highly loaded components and engines with flat-tappet cam technology. SPRINT 20W-50 utilises a powerful detergent and dispersant designed to suspend, carry and remove unwanted deposits back to the oil filter to prevent the circulation of debris, build-up of varnish deposits and agglomeration of sludge. Suitable for use in all seasons, saving the need to change between winter and summer grade engine oils.

Recommended by Aztec Oils as suitable for the following applications

API SJ/CF

Ideal for performance classic engines that are subject to high loads. Suitable for track, fast-road and road use.

Benefits

- Advanced anti-wear technology helps to protect engine components.
- Excellent shear stability for stay-in-grade performance.
- High levels of ZDDP (zinc/phosphorus) anti-wear protection for cam lobes & flat-tappets.
- Modern additive technology for vehicles equipped with filtration systems.
- Prevents corrosion, varnish deposits & the agglomeration of sludge.
- Reliable cold starting.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.882
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	158
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	18.5
Pour Point (°C)	ASTM D97	-30
Total Base Number (mg KOH/g)	ASTM D2896	11
Viscosity Index	ASTM D2207	132
ZDDP Concentration (Average)		1500ppm

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.