


EMPROTEC GEO NBG-L 40

Product Code: GEO001 | **Revision:** 20240821



A premium low ash gas engine oil.

Available Pack Sizes



Applications

Formulated with the highest quality Group II base oils and utilising the latest low ash technology to achieve excellent levels of protection whilst being able to maintain outstanding cleanliness under severe operating conditions. EMPROTEC GEO NBG-L 40 neutralises harmful acids to protect engine components from corrosion through its superior base number retention and is compatible with exhaust gas treatment systems.

Manufacturer Approvals

Caterpillar CG Gas Engines
MWM TCG Gas Engines

Recommended by Aztec Oils as suitable for the following applications

Caterpillar G3516 Tale Engines
Cummins QSK60S
INNIO Jenbacher Type 2, 3, 4 (versions A&B), Type 6 (versions C&E) Natural Gas (Class A)
INNIO Jenbacher Type 2, 3, 4 (versions A&B), Type 6 (versions C&E) Biogas (Class A)
MAN M 3271-2
MWM Natural Gas
MWM Biogas
Rolls-Royce B35:40, C26:33, K-G1/G2/G3/G4
Wärtsilä DF Engines (Up to 25% diesel)
Wärtsilä SG Engines
Suitable for Tendom

Suitable to use in power generation plants where a low ash content (up to 0.55%) is accepted by the manufacturer.

Benefits

- Advanced TBN retention to improve engine durability and maintain performance.
- Excellent thermal stability at high temperatures.
- Extended drain capabilities.
- Increased protection against wear and corrosion.
- Very low piston deposit and varnish formation.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.88
Flash Point (°C)	ASTM D92	>230
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	123.9
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	110
Pour Point (°C)	ASTM D97	-12
Sulphated Ash (wt%)	ASTM D874	0.5
Total Base Number (mg KOH/g)	ASTM D2896	5.7
Viscosity Index	ASTM D2207	110

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the equipments maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- NB: Engines that are being fuelled with sour gases may not benefit from low ash technology.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.