THE LUBRICATION SPECIALISTS	Produced in the UK Produced in t

Applications

A high-quality multipurpose extreme pressure grease

VOLCATEC LITHIUM EP 2

Product Code: GRE001 Revision: 20231023	for use in all anti-friction and plain bearings subjected to high load conditions. Used extensively for applications throughout agricultural, automotive, commercial, off-highway and industrial sectors.
AZTEC OLS	Recommended by Aztec Oils as suitable for the following applications
High Performance Grease	DIN 51502 KP2N-30 ISO 6743-9 L-XCDHB2 Can be applied manually, by using a standard grease gun or via a central lubricating system capable of pumping an NLGI 2 grease.
Multipurpose & extreme pressure lithium based grease.	Check compatibility with the grease applied previously & if necessary purge system prior to application. Care should be taken not to over-lubricate & apply the quantity of grease recommended by the manufacturer.
Multipulpose & extreme pressure ittilum based grease.	Benefits
Available Pack Sizes	 Excellent extreme pressure & anti-wear performance. Good adhesive properties. Highly versatile multipurpose grease. Resistant to water washout & protects from corrosion. Smooth texture & good pumpability. Very good thermal stability & resistant to temperature variations.
50 KG KG	
Typical Test	Data

Typical Test Data		
Appearance	Smooth grease	
Base Oil	Mineral	
Base Oil Viscosity @ 40°C (mm/s ²)	150	
Colour	Brown	
Copper Corrosion	1b	
Dropping Point (°C)	>180	
Four Balll Weld Load (Kg)	280	
NLGI Classification	2	
Oil Separation - 42hrs @ 40°C (%)	1.7	
Oil Separation - 168hrs @ 40°C (%)	3.7	
Operating Temperature Range (°C)	-30 to +140	
Thickener	Lithium soap	
Worked Penetration 0.1mm	265-295	

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

specification.

Health, Safety & Recommendations

THE LUBRICATION SPECIALISTS

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Avoid contamination of the grease by dust and dirt when applying.
- Before using this product, the maintenance guide should be checked and lubrication intervals must be carried out in accordance with the manufacturers' recommendations.
- Not all greases are compatible, check compatibility with the grease applied previously and if necessary purge the system prior to application.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.