

TRANSMATEC ATF D III

Product Code: GTO001 | **Revision:** 20250502



Part synthetic automatic transmission & power steering fluid.

Available Pack Sizes



Applications

A high-quality automatic transmission fluid which demonstrates excellent frictional stability and extreme pressure characteristics to ensure confidence in passenger cars and heavy duty equipment throughout its long service life. Formulated from highly refined base stocks and additive technology designed to impart excellent oxidation resistance and anti-wear properties.

Recommended by Aztec Oils as suitable for the following applications

Allison C4
Daimler Trucks: DTFR 13C100 (MB 236.1), DTFR 13C140 (MB 236.7), DTFR 13C170 (MB 236.9)
Caterpillar TO-2
Ford Mercon
GM Dexron IIIIG
MAN 339 Z1, V1, Z2, V2
Mercedes-Benz 236.5, 236.6
Voith 55.6335, 55.6636
Volvo 97340, 97341
ZF TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 14B, 16L, 17C

Not suitable to use where fluid type Ford M2C33F or G is required.

Benefits

- Excellent high temperature operation stability.
- Good seal compatibility.
- Low temperature fluidity.
- Maintains constant frictional performance.
- Protects against wear, sludge and corrosion and offers excellent shear stability.
- Smooth operation of power transmissions and power steering systems.
- Superb oxidation stability.

Typical Test Data

Appearance		Clear & bright, red
Density @ 15°C (kg/m ³)	ASTM D4052	0.84
Flash Point (°C)	ASTM D92	>180
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	34
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	7.7
Pour Point (°C)	ASTM D97	<-40
Viscosity Index	ASTM D2207	200

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.