

## TRANSMATEC ATF D II

**Product Code:** GTO002 | **Revision:** 20250502



Mineral oil based automatic transmission & power steering fluid.

### Available Pack Sizes



### Applications

A quality automatic transmission fluid which demonstrates excellent frictional stability and extreme pressure characteristics to ensure confidence in passenger cars and heavy duty equipment throughout its long service life. Formulated from highly refined base stocks and additive technology designed to impart excellent oxidation resistance and anti-wear properties.

Recommended by Aztec Oils as suitable for the following applications

Allison C4  
Caterpillar TO-2  
Daimler Trucks DTFR 13C100 (MB 236.1), DTFR 13C140 (MB 236.7)  
Ford Mercon, M2C138-CJ, M2C166-H  
GM Dexron II, IID  
ZT TE-ML 09, 11, 14  
Suitable to use in hydrostatic transmissions, power steering systems and hydraulic applications where GM DEXRON IID is required.

Not suitable to use where fluid type Ford M2C33F or G is required.

### Benefits

- Good long-term anti-wear protection.
- Good seal compatibility.
- High viscosity index allows the fluid to be used in applications with a wide temperature range.
- Protects against wear, sludge and corrosion and offers excellent shear stability.
- Suitable for most automatic transmissions and power steering systems.

### Typical Test Data

Appearance		Clear & bright, red
Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.84
Flash Point (°C)	ASTM D92	>180
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	39
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	7.8
Pour Point (°C)	ASTM D97	<-40
Viscosity Index	ASTM D2207	175

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

## Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.