

TRANSMATEC SS-5 75W-90

Product Code: GTO022 | **Revision:** 20240820



Semi synthetic high-performance transmission oil.

Available Pack Sizes



Applications

A high-performance heavy duty semi synthetic automotive gear oil, offering higher levels of performance when compared to straight mineral oils. Contains an EP additive system designed to withstand challenging working environments including high speeds and high shock loads.

Recommended by Aztec Oils as suitable for the following applications

API GL-5
ZF TE-ML 05

For use in high performance manual transmissions, spiral bevel axles, high load drive axles, hypoid axles and steering units. This product will often smooth and improve manual gear changes in previously "notchy" gear boxes although it is not suitable for synchronised gears.

Benefits

- Compatible with most elastomers and seal materials.
- Good oxidation stability to provide resistance to aging.
- Exceptional anti-wear protection.
- Long service life.
- Superb protection against rust and corrosion.

Typical Test Data

Density @ 15°C (kg/m³)	ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm²/s)	ASTM D445	75
Kinematic Viscosity @ 100°C (mm²/s)	ASTM D445	15
Pour Point (°C)	ASTM D97	<-25
Viscosity Index	ASTM D2207	212

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.