


TRANSMATEC TRANS-4 50

Product Code: GTO029 | **Revision:** 20240820



Specialist mineral oil based fluid for hydraulics and transmission components.

Available Pack Sizes



Applications

A monograde fluid to meet the requirements of transmissions found in off-highway, construction and earthmoving equipment. Blended from quality base oils with performance additives these fluids are designed to provide improved frictional properties, anti-wear performance and oxidation stability leading to longer equipment life.

Recommended by Aztec Oils as suitable for the following applications

Allison C4
Caterpillar TO-4
ZF TE-ML 03C

Benefits

- Excellent sludge control.
- Good long-term anti-wear protection.
- Good seal compatibility.
- Longer equipment life.
- Improved friction properties for use with oil immersed frictional disks.
- Suitable for a wide range of off-highway equipment.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.89
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	179
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	17.2
Pour Point (°C)	ASTM D97	<-20
Viscosity Index	ASTM D2207	103

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.



AZTEC OILS

THE LUBRICATION SPECIALISTS



Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- Not to be used as an engine lubricant.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.