

## TRANSMATEC FS-4 75W-80

Product Code: GTO041 | Revision: 20240820



Fully synthetic high-performance transmission oil.

### Available Pack Sizes



### Applications

A fully synthetic high performance gear oil manufactured from a blend of high quality base oils, sheer stable viscosity index improvers and a multipurpose extreme pressure additive system. It offers a high level of performance when compared to straight mineral oil whilst remaining compatible with mineral oils, enabling it to be simply used as a replacement product on a drain and fill basis.

Recommended by Aztec Oils as suitable for the following applications

API GL-4  
Daimler Trucks DTFR 13B170 (MB 235.5)  
MAN 341 Type Z1, Z2, E1  
MTF 94  
MIL-L-2105  
Volvo 97305, 97307  
ZF TE-ML 02A, 02B, 16K

### Benefits

- Compatible with most elastomers and seal materials.
- Does not foam under extreme loads.
- Superb protection against rust and corrosion.
- Low temperature fluidity.
- Offers improved shift comfort.
- Outstanding oxidation stability to provide resistance to aging.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.85
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	42.6
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	10
Pour Point (°C)	ASTM D97	-40
Viscosity Index	ASTM D2207	230

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

## Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.