

AGRITEC EP-4 85W-140 WBS

Product Code: GTO043 | **Revision:** 20240819



Specialised heavy duty gear oil.

Available Pack Sizes



Applications

A premium specialised gear oil for agricultural and off-highway equipment, blended from highly refined base oils of low aromatisation and a carefully selected additive technology with extreme pressure capabilities. Ideally suited for spiral bevel gears to operate under moderate to severe conditions or hypoid gears operating under moderate speeds and loads.

Recommended by Aztec Oils as suitable for the following applications

API GL-4
New Holland 600 TR
ZF 05F, 06K, 21F

Benefits

- Engineered to have good oxidation resistance, thermal stability and superb low temperature performance.
- Excellent brake squawk and chatter suppression.
- Exceptional anti-wear properties.
- Oil immersed wet brake compatible.
- Provides constant frictional performance.

Typical Test Data

| | | |
|--|------------|------|
| Density @ 15°C (kg/m ³) | ASTM D4052 | 0.89 |
| Flash Point (°C) | ASTM D92 | >200 |
| Kinematic Viscosity @ 40°C (mm ² /s) | ASTM D445 | 350 |
| Kinematic Viscosity @ 100°C (mm ² /s) | ASTM D445 | 26 |
| Pour Point (°C) | ASTM D97 | <-20 |
| Viscosity Index | ASTM D2207 | 98 |

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the equipment's maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.