

TRANSMATEC ATF D VI

Product Code: GTO045 | **Revision:** 20240902



Synthetic low viscosity automatic transmission fluid.

Available Pack Sizes



Applications

An exceptional ATF for use in vehicles with automatic transmissions. Designed to protect your transmission through improved oxidation resistance, friction durability, shear stability and superb wear protection. Engineered using the latest additive technology to provide a consistent and responsive shift throughout the life of the oil to protect your vehicle transmissions for longer than previous Dexron type fluids.

Recommended by Aztec Oils as suitable for the following applications

Aisin Warner AW-1, AW-2, JWS 3309 (T-IV), JWS 3324 (WS)
Allison C4
Ford WSS-M2C922-A1, WSS-M2C924-A (XT-8-QAW)
GM Dexron VI
Honda Z-1 (Not CVT), DW-1
JASO M315-2013 1-A-LV
Mazda ATF 3317, FZ, MV
Nissan Matic J, K, S
ZF TE-ML 09, 11A, 11B, 21L
ZF 5 & 6 speed transmissions

Not suitable for vehicles with DCT or CVT transmissions.

Benefits

- Enhanced additive technology for greater vehicle coverage.
- Improved anti-wear protection for extended service intervals.
- Low viscosity to reduce frictional losses through the transmission to help improve fuel economy.
- Optimised frictional characteristics that provide smooth gear shifting.
- Outstanding resistance against sludge & deposit formation.
- Superb low temperature performance.

Typical Test Data

Appearance		Clear & bright, red
Density @ 15°C (kg/m ³)	ASTM D4052	0.85
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	29
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	6.0
Pour Point (°C)	ASTM D97	-43
Viscosity Index	ASTM D2207	160

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.