


## TRANSMATEC SS-5 75W-90 LS

**Product Code:** GTO048 | **Revision:** 20240820



Semi synthetic limited-slip axle oil.

### Available Pack Sizes



### Applications

A semi synthetic gear oil manufactured from a blend of high quality base oils and sophisticated additive technology to withstand high loads in limited slip differentials. Advanced friction modifiers help to reduce chatter and improve traction to provide a longer service life. Suitable to use in differentials, final drives, gear driven transfer cases and other transmission applications where an SAE 75W-90 extreme pressure gear lubricant is required.

### Recommended by Aztec Oils as suitable for the following applications

API GL-5 LS  
ZF TE-ML 05D, 21C

Designed for limited slip differentials but can also be used in conventional differential applications where an API GL-5 75W-90 or 80W-90 is required.

### Benefits

- Exceptional shear and thermal stability
- Excellent oxidation stability to provide resistance to aging.
- Helps to reduce differential noise and chatter.
- Long drain intervals.
- Superb protection against rust and corrosion.
- Outstanding load carrying capacity.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	95
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	15
Pour Point (°C)	ASTM D97	<-25
Viscosity Index	ASTM D2207	166

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- Not recommended for chain driven transfer cases.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.



# AZTEC OILS

THE LUBRICATION SPECIALISTS



In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.