

TRANSMATEC ATF G

Product Code: GTO054 | **Revision:** 20240820



Specialised mineral oil based automatic transmission fluid.

Available Pack Sizes

20L

205L

Applications

Formulated from highly quality paraffinic base oils and unique additive technology. This product has been designed to provide protection to critical parts by providing corrosion and oxidation resistance preventing the formation of deposits and varnishes. Suitable for use in Ford cars manufactured between 1976 to 1981 specifying a high friction fluid compliant with the Ford ESW-M2C33 Type F or G specification.

Recommended by Aztec Oils as suitable for the following applications

Ford ESW-M2C33F, G

Suitable for use in automatic transmissions, torque converters, power steering units and hydraulic pumps specifying the Ford ESW-M2C33F and G specification.

Benefits

- Good seal compatibility.
- Excellent anti-wear characteristics.
- Suitable for other transmissions where a non-friction modified fluid is required.

Typical Test Data

Appearance		Clear & bright, red
Density @ 15°C (kg/m ³)	ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>180
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	40
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	7.9
Pour Point (°C)	ASTM D97	<-30
Viscosity Index	ASTM D2207	174

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.