

AGRITEC HP-PRO

Product Code: GTO071 | **Revision:** 20241115



High performance & heavy duty transmission oil for axles with oil immersed brakes.

Available Pack Sizes

20L

60L

205L

Applications

A high-performance transmission oil for agricultural and off-highway equipment requiring a specialised lubricant combining enhanced additive technology with exceptional anti-squawk characteristics in heavily loaded axles with oil immersed braking systems. Successful real-world trials have demonstrated AGRITEC HP-PRO to be a problem solver in chattering axles.

Recommended by Aztec Oils as suitable for the following applications

API GL-4
Alternative where JCB Standard 4000/2200, 4000/2202 or 4000/2205 is specified.
Suitable for Komatsu, Manitou & Thwaites.

Benefits

- Allows for rationalisation of products.
- Highly resistance against aeration & foaming.
- Engineered to have good oxidation resistance, thermal stability.
- Exceptional brake squawk and chatter suppression.
- Provides consistent frictional performance.
- Used in heavily loaded applications where superb brake-chatter suppression is required.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.88
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	82
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	10.9
Pour Point (°C)	ASTM D97	-20
Viscosity Index	ASTM D2207	120

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the equipment's maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.