


TRANSMATEC TRANS-4 60

Product Code: GTO074 | **Revision:** 20230802



Specialist mineral oil based fluid for transmission & drive train components.

Available Pack Sizes



Applications

A specialised monograde fluid, designed to meet the requirements of transmission and drive train components found in off-highway, construction and earthmoving equipment. Formulated using high-quality base oils with performance additive technology, these fluids are designed to provide improved frictional properties, anti-wear performance and oxidation stability to reduce maintenance costs and offer a long service life.

Recommended by Aztec Oils as suitable for the following applications

Allison C4
Caterpillar TO-4
ZF TE-ML 03C

Benefits

- Designed for high ambient temperature applications.
- Durable anti-wear protection.
- Excellent sludge control.
- High viscosity reduces gear wear to promote a long component life.
- Improved friction properties for use with oil immersed brakes & frictional disks.
- Promotes minimal clutch slippage, smooth & quiet brake operation.

Typical Test Data

| | | |
|--|------------|-------|
| Density @ 15°C (kg/m ³) | ASTM D4052 | 0.906 |
| Flash Point (°C) | ASTM D92 | >220 |
| Kinematic Viscosity @ 40°C (mm ² /s) | ASTM D445 | 332 |
| Kinematic Viscosity @ 100°C (mm ² /s) | ASTM D445 | 25.99 |
| Pour Point (°C) | ASTM D97 | <-15 |
| Viscosity Index | ASTM D2207 | 102 |

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- Not to be used as an engine lubricant.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.