


## EMPROTEC FLEET 15W-40

**Product Code:** HDD003 | **Revision:** 20250624



Heavy duty mixed fleet engine oil, ACEA E3, API CH-4.

### Available Pack Sizes



### Applications

A multi-grade heavy duty engine oil for inter-city or long-haul engines in buses, commercial, plant and industrial equipment where Euro III & II emission compliance is required. Manufactured from quality mineral oil, robust additives and our specialist Adaptive Molecular Technology to enhance the power and efficiency of your vehicle to help maintain peak reliability, ensuring maximum performance for the older mixed fleet.

### Recommended by Aztec Oils as suitable for the following applications

ACEA E3  
API CH-4  
Caterpillar ECF-1  
Cummins 20072  
Deutz DQC II-10  
Mack EO-L  
MAN 271  
Mercedes-Benz 228.1  
MTU Type 1.0  
Volvo VDS-2

### Benefits

- Anti-wear performance for reduced engine wear.
- Excellent thermal stability provides resistance against oxidation.
- High shear stability for stay in grade performance.
- Ideal mixed fleet lubricant.
- Improved bore polishing protection.
- Utilises detergent & dispersant technology for excellent engine cleanliness.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.886
Flash Point (°C)	ASTM D92	225
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	105
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	14.2
Pour Point (°C)	ASTM D97	-30
Total Base Number (mg KOH/g)	ASTM D2896	10.2
Viscosity Index	ASTM D2207	138

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

## Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.