

HYDRATEC LHM FLUID

Product Code: MAI002 | **Revision:** 20240821



Specially formulated mineral hydraulic & brake fluid.

Available Pack Sizes



1L



5L



20L



205L

Applications

LHM Fluid is manufactured from specialised mineral oil and selected additive technology to produce a hydraulic and brake fluid with a very high viscosity index. Specifically designed for use in Citroen vehicles with hydro-pneumatic suspension and brakes. This grade is designed to protect against pump wear and provide good rates of flow throughout the system even in arduous conditions.

Recommended by Aztec Oils as suitable for the following applications

Fiat 9.55597
Ford ESN-M6C59A
ISO 7308
PSA B71 2710

Suitable to use as a mineral hydraulic fluid in Audi, Citroen and certain Jaguar applications or systems using green mineral oil.

Benefits

- Excellent corrosion resistance.
- Outstanding anti-wear & anti-oxidant properties.
- Provides excellent lubricity.
- Suitable for use in systems with pressure up to and in excess of 150bar.
- Superb hydrolytic stability.
- Very high viscosity index to give performance over a wide temperature range.

Typical Test Data

Appearance		Clear & bright, green fluid
Density @ 15°C (kg/m ³)	ASTM D4052	0.84
Flash Point (°C)	ASTM D92	>130
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	17
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	6.1
Pour Point (°C)	ASTM D97	<-50
Viscosity Index	ASTM D2207	350

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using the product, it is advised to consult the vehicle handbook for the correct fluid type.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- Never use this fluid in reservoirs painted black and those systems using vegetable or synthetic based fluids.
- Not miscible or compatible with synthetic fluids including DOT 3, DOT 4, DOT 5, DOT 5.1 and former Citroen fluids.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.