

## HYDRATEC POWER STEERING FLUID

**Product Code:** MAI005 | **Revision:** 20240819



Mineral oil based universal power steering fluid.

### Available Pack Sizes



1L



5L

### Applications

A premium quality universal power steering and hydraulic fluid designed to protect the power steering pump against wear, reduce pump whine and help maintain a long system life. Formulated from highly refined base stocks and advanced additive technology for excellent oxidation and anti-foam resistance. Compatible with seal materials to help prevent leaks.

### Recommended by Aztec Oils as suitable for the following applications

Most power steering systems where a red ATF type fluid is specified.  
Always follow the vehicle manufacturer's recommendations.

Not to be used in systems that require CHF fluid.

### Benefits

- Helps keep power steering systems operating smoothly & quietly.
- Highly resistant to foaming & oxidation.
- Good seal compatibility to reduce & prevent leaks.
- Protects against wear, sludge & corrosion.
- Provides a long service life.
- Suitable for most power steering systems.

### Typical Test Data

Appearance		Clear & bright, red
Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.84
Flash Point (°C)	ASTM D92	>180
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	39
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	7.8
Pour Point (°C)	ASTM D97	<-40
Viscosity Index	ASTM D2207	175

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

## Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.