

## TOROTEC FLUSHING OIL

**Product Code:** MON003 | **Revision:** 20250722



A quality engine flushing oil primarily designed for use as a crankcase flushing oil in petrol & diesel engines prior to replenishment with new oil.

### Available Pack Sizes



### Applications

A specially formulated blend of high-quality paraffinic mineral oil and advanced additive technology, designed to clean internal engine components by removing carbon deposits, varnish and sludge. This engine flush dissolves combustion by-products and accumulated residues, while strong detergents neutralise corrosive acids often left behind in used oil. Primarily suitable for petrol and diesel engines, it is also effective in hydraulic systems, circulating oil systems and certain gearbox applications, helping to restore cleanliness and optimise overall system performance.

### Recommended by Aztec Oils as suitable for the following applications

1. Run the engine or system until it reaches operating temperature.
2. Drain the old oil.
3. Fill with TOROTEC FLUSHING OIL, keeping between min & max fill levels.
4. Run the system without load for 10 to 15 minutes.
5. Drain flushing oil, repeat above steps if necessary.
6. Refill with the vehicle or system with the recommended Aztec Oils lubricant.

Strickly for short term use as a flushing oil, it is not advisable for long term use.

### Benefits

- Can be used if the system lubricant has to be drained due to a contamination problem.
- Excellent anti-wear protection.
- Ideal for use where a vehicles history is unknown.
- Not aggressive on seals as per chemical engine flushes.
- Powerful detergent & dispersant technology to remove built-up deposits.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	39
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	6.1
Pour Point (°C)	ASTM D97	-33
Total Base Number (mg KOH/g)	ASTM D2896	8.4
Viscosity Index	ASTM D2207	100

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

## Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.