

EMPROTEC DETROIT 40 LA

Product Code: MON029 | **Revision:** 20250630



Monograde low ash mineral engine oil for two-stroke diesel engines.

Available Pack Sizes



Applications

A low ash monograde engine oil that has been specially formulated for heavy duty two-stroke diesel engines (Detroit Diesel). Manufactured from high-quality base oils and compounded with additives, providing excellent lubrication under the most severe operating conditions. Containing detergent/dispersant, anti-oxidation and anti-wear additives, ensuring minimal combustion chamber and valve deposits.

Recommended by Aztec Oils as suitable for the following applications

API CF-2

Recommended for use in heavy duty (turbo-charged), high-speed, two-cycle engines, operating under severe conditions where an API CF-2 is specified.

Benefits

- Excellent anti-wear & anti-corrosion properties.
- High stability in operation.
- Low sulphated ash content.
- Superb oxidation and foaming resistance.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.88
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	130
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	13.8
Pour Point (°C)	ASTM D97	<-15
Total Base Number (mg KOH/g)	ASTM D2896	7.2
Viscosity Index	ASTM D2207	102

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.