

DX-3 40+

Product Code: MON036 | **Revision:** 20250630



Heavy duty monograde mineral based locomotive engine oil.

Available Pack Sizes



Applications

Heavy duty monograde engine oils, manufactured from high quality mineral base oils and superior additive technology. Provides protection from wear, corrosion and oxidation in turbo charged and naturally aspirated diesel locomotive engines.

Recommended by Aztec Oils as suitable for the following applications

API CF-4

Benefits

- Powerful detergent/dispersant additive technology.
- Protection against wear and corrosion.
- Suitable for turbo charged and naturally asperated diesel engines.
- Suitable for use in engines, transmissions and hydraulic systems where the use of a monograde engine oil is specified.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.89
Flash Point (°C)	ASTM D92	>220
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	135
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	13.9
Pour Point (°C)	ASTM D97	<-15
Total Base Number (mg KOH/g)	ASTM D2896	8.4
Viscosity Index	ASTM D2207	100

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.