	ION SPECIALISTS	
MOTOTEC ENDURANCE 5W-30	Applications	
Product Code: MOT026 Revision: 20250310	A high-performance fully synthetic four stroke engine oil blended from unique additive technology and synergistically combining our Ester Driven Technology. Specifically designed for optimum protection against wear and deposit control by utilising special additives to create a protective layer to ensure smooth gear changes and guarantee optimal cleanliness of engine and gearbox components. Providing the ultimate protection throughout adventurous and inner-city driving conditions.	
Northance Styles Styles Westing Manual Annore Styles Manual Annore Manual Annore Manua	Recommended by Aztec Oils as suitable for the following applications	
High-performance fully synthetic four stroke motorcycle	API SN, SM, SL, SJ JASO MA, MA2 Suitable for Aprilla, BMW Motorrad, Ducati, Gasgas, Honda, Kawasaki, KTM, MBK, Moto Guzzi, Peugeot, Suzuki, Sym, Triumph & Yamaha. Suitable for air & water cooled 4T scooters.	
& scooter oil.	Benefits	

11	4L 20L	60L	205L

Available Pack Sizes

 Advanced engine, gear & wet clutch protection under the most demanding of conditions.

- Compatible with catalytic converters.
 Designed for modern 4-stroke scooters & maxiscooters.
- Enhanced throttle response & acceleration.
- Exceptional deposit control & engine cleanliness.
- Extraordinary fluidity at low temperatures & exceptional film strength at high temperatures.
- Outstanding shear stability to prevent viscosity break down.
- Proven trials demonstate a sustained improvement in clutch control throughout the drain interval.
- Superb oxidation & thermal stability.

Typical Test Data					
Appearance		Clear & bright, amber			
Density @ 15°C (kg/m ³)	ASTM D4052	0.851			
Flash Point (°C)	ASTM D92	>210			
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	69.8			
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	11.5			
Pour Point (°C)	ASTM D97	-40			
Viscosity Index	ASTM D2207	160			

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.



THE LUBRICATION SPECIALISTS

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
 This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.