

MOTOTEC ATV 10W-40 SS

Product Code: MOT028 | **Revision:** 20250117



Professional ATV & quad bike semi synthetic engine oil.

Available Pack Sizes



Applications

A highly advanced semi-synthetic four-stroke oil for ATVs and UTVs, designed for use with or without wet clutches and emission control devices. Fortified with our Adaptive Molecular Technology to further enhance your motorcycles power, efficiency and rideability both on and off the road. Incorporates detergent and dispersant additives to maintain engine cleanliness and deposit control.

Recommended by Aztec Oils as suitable for the following applications

API SL, SJ, SH, SG
JASO MA2
Suitable for Aeon, Can-am, CF MOTO, Honda, Kawasaki, Linhai, Suzuki & Yamaha.

Benefits

- Compatible with catalytic converters.
- Excellent shear stability to prevent viscosity break down.
- Exceptional anti-wear properties protect camshafts & bearings.
- Good clutch control & performance.
- Highly resistant to oxidation & thermal degradation.
- Provides protection to the engine, gearset & wet clutch, even under demanding conditions.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.857
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	82
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	13
Pour Point (°C)	ASTM D97	-30
TBN		8
Viscosity Index	ASTM D2207	155

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.