

MOTOTEC X-RACE 15W-50

Product Code: MOT029 | **Revision:** 20250310



High-performance synthetic technology four stroke motocross oil.

Available Pack Sizes



Applications

An advanced engine oil with synthetic performance designed to meet the extreme demands of motocross racing. Blended from the latest additive and Ester Driven Technology to work in synergy with your engine to give the rider maximum performance, enhanced power, great feel and rideability off-road. Designed to provide the highest level of protection against engine wear and oxidation whilst being highly shear stable, this means you can rely on this oil to stay in grade and provide that critical oil film to protect all the moving parts. Through extensive development and testing we have produced a precise balance between providing excellent lubrication, superb clutch response and smooth gear changes.

Recommended by Aztec Oils as suitable for the following applications

API SN, SM, SL, SJ
JASO MA2
Suitable for Gasgas, Kawasaki, KTM, Suzuki & Yamaha.

Benefits

- Advanced engine, gear & wet clutch protection under the most demanding of conditions.
- Compatible with catalytic converters.
- Enhanced throttle response & acceleration.
- Exceptional deposit control & engine cleanliness.
- Outstanding shear stability to prevent viscosity break down.
- Proven trials demonstrate a sustained improvement in clutch control.
- Robust lubrication film strength at high temperatures.
- Superb oxidation & thermal stability.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.868
Flash Point (°C)	ASTM D92	>240
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	135
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	18
Pour Point (°C)	ASTM D97	-30
TBN		6.8
Viscosity Index	ASTM D2207	149

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.