

MOTOTEC CLASSIC 2-STROKE

Product Code: MOT031 | **Revision:** 20250303



Mineral based two stroke oil for classic motorcycles.

Available Pack Sizes



Applications

Low ash two stroke engine oil for classic two stroke motorcycles manufactured from high-quality mineral base oils and blended with specially selected detergent and dispersant additives. Particularly formulated to provide good lubricity, promote easy starts, help prevent spark plug whiskering and protect from corrosion. It is suitable for both premix and injector systems including air and water cooled two stroke engines.

Recommended by Aztec Oils as suitable for the following applications

API TC
ISO-L-EGB
JASO FB
MIL-L-2104B

Mix with petrol in the ratio recommended by the equipment manufacturer.

Benefits

- Clean burn characteristics help reduce carbon build-up and reduce smoke emissions.
- Excellent deposit and wear control.
- Low ash for reduced deposit formation.
- Protects against piston and cylinder scuffing.
- Promotes easy starting.
- Readily miscible in petrol.

Typical Test Data

Appearance		Clear & bright, red
Density @ 15°C (kg/m ³)	ASTM D4052	0.879
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	58
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	8.2
Pour Point (°C)	ASTM D97	<-20
Sulphated Ash (%)	ASTM D874	0.6
Total Base Number (mg KOH/g)	ASTM D2896	0.6
Viscosity Index	ASTM D2207	110

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.