

MOTOTEC CLASSIC 50

Product Code: MOT033 | **Revision:** 20250310



Non-detergent/dispersant monograde classic motorcycle oil.

Available Pack Sizes



Applications

High-quality monograde engine oil specifically designed for veteran, vintage and classic motorcycles with a metal gauze oil filter which specify the use of a non-detergent/dispersant and a low TBN lubricant to allow any dirt, debris or sludge to drop into the engines sump and not recirculate where it could potentially damage critical components.

Recommended by Aztec Oils as suitable for the following applications

API SB/CA
Suitable for BMW, BSA, Ratier, Norton & Triumph.

Benefits

- Designed for veteran, vintage and classic motorbikes.
- Good anti-wear characteristics.
- Suitable for petrol and diesel engines without modern filtration systems.
- Superior resistance against rust and oxidation.

Typical Test Data

| | | |
|--|------------|-----------------------|
| Appearance | | Clear & bright, amber |
| Density @ 15°C (kg/m ³) | ASTM D4052 | 0.90 |
| Flash Point (°C) | ASTM D92 | >200 |
| Kinematic Viscosity @ 40°C (mm ² /s) | ASTM D445 | 215 |
| Kinematic Viscosity @ 100°C (mm ² /s) | ASTM D445 | 19 |
| Pour Point (°C) | ASTM D97 | <-6 |
| Total Base Number (mg KOH/g) | ASTM D2896 | 3.0 |
| Viscosity Index | ASTM D2207 | 99 |

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.