

MOTOTEC TOURING 10W-40 SS

Product Code: MOT035 | **Revision:** 20250109



High-quality semi synthetic four stroke motorcycle oil.

Available Pack Sizes



Applications

A durable semi synthetic four stroke oil for on and off road motorcycles, based on a blend of high-performance synthetic oils, high-quality mineral base stocks and synergistically combining our Adaptive Molecular Technology to further enhance the power, efficiency and rideability of your motorcycle. Offers superb lubricity and anti-wear protection to minimise wear throughout the drivetrain and engine, an excellent wet clutch response allows for easier and smoother gear shifts.

Recommended by Aztec Oils as suitable for the following applications

API SL, SJ, SH, SG
JASO MA2
API SL, SJ, SH, SG; JASO MA2; Suitable for BMW Motorrad, Gasgas, Honda, Kawasaki, MBK, Moto Guzzi, Suzuki, Sym & Yamaha.

Benefits

- Compatible with catalytic converters.
- Exceptional anti-wear properties protect camshafts & bearings.
- Excellent oxidation & thermal stability.
- Good shear stability to prevent viscosity break down.
- Incorporates detergent & dispersant technology for excellent engine cleanliness & deposit control.
- JASO MA2 guarantees clutch engagement during starting, acceleration & constant speed.
- Provides protection to the engine, gearset & wet clutch, even under demanding conditions.
- Proven trials demonstrate sustained acceleration & improved drivability.
- Suitable for use with ATV/quad bikes.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	82.2
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	12.9
Pour Point (°C)	ASTM D97	-28
TBN		8
Viscosity Index	ASTM D2207	156

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.