

MOTOTEC TOURING 10W-30 SS

Product Code: MOT036 | **Revision:** 20250821



Semi synthetic four stroke motorcycle oil.

Available Pack Sizes



Applications

A premium semi-synthetic four stroke motorcycle oil, formulated from a blend of advanced synthetic components and high-quality mineral base stocks. Enhanced with our Adaptive Molecular Technology, it dynamically responds to your engine's needs to maximise power, improve efficiency and enhance overall rideability. Engineered to deliver exceptional lubricity and robust anti-wear protection, it reduces friction and extends engine life, even under the most demanding riding conditions. With excellent thermal and oxidative stability, it ensures consistent performance and reliability on both road and off-road terrain. Outstanding wet clutch compatibility provides smooth gear shifts, responsive acceleration and total riding confidence.

Recommended by Aztec Oils as suitable for the following applications

API SL, SJ, SH, SG
JASO MA2
Suitable for BMW Motorrad, Gasgas, Honda, MBK, Moto Guzzi, Suzuki, Sym & Yamaha.

Benefits

- Compatible with catalytic converters.
- Exceptional anti-wear properties.
- Excellent oxidation & thermal stability.
- Good shear stability to prevent viscosity break down.
- JASO MA2 guarantees clutch engagement during starting, acceleration & constant speed.
- Provides protection to the engine, gearset & wet clutch, even under demanding conditions.
- Proven trials demonstrate sustained acceleration & improved drivability.
- Suitable for use with ATV/quad bikes.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.854
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	64.2
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	10.4
Pour Point (°C)	ASTM D97	<-25
TBN		8
Viscosity Index	ASTM D2207	151

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.