

## MOTOTEC ENDURANCE 10W-60

**Product Code:** MOT043 | **Revision:** 20230919



High-performance fully synthetic four stroke motorcycle oil.

### Available Pack Sizes

1L

4L

20L

60L

205L

### Applications

A high-performance four stroke racing engine oil blended from fully synthetic oils, unique additive technology and synergistically combining our Ester Driven Technology to further enhance the power, efficiency and rideability of your motorcycle. Special additives create a protective layer to ensure smooth gear changes and guarantee optimal cleanliness of engine and gearbox components for optimum protection against wear and the build-up of deposits. The chosen viscosity maintains a hydrodynamic lubrication film to protect from wear at high-RPM, providing the ultimate protection on the road or race track.

Recommended by Aztec Oils as suitable for the following applications

API SN, SM, SL, SJ  
JASO MA, MA2  
Suitable for Aprilla, BMW Motorrad, Ducati, Gasgas, Honda, Kawasaki, KTM, MBK, Moto Guzzi, Peugeot, Suzuki, Sym, Triumph & Yamaha.

### Benefits

- Enhanced throttle response & acceleration.
- Exceptional deposit control & engine cleanliness.
- Extraordinary fluidity at low temperatures & exceptional film strength at high temperatures.
- Advanced engine, gear & wet clutch protection under the most demanding of conditions.
- Compatible with catalytic converters.
- Outstanding shear stability to prevent viscosity break down.
- Proven trials demonstrate a sustained improvement in clutch control throughout the drain interval.
- Superb oxidation & thermal stability.
- Suitable for use with ATV/quad bikes.

### Typical Test Data

Appearance		Clear & bright
Density @ 15°C	ASTM D4052	0.858
Flash Point (°C)	ASTM D92	>220
Kinematic Viscosity @ 40°C (mm/s <sup>2</sup> )	ASTM D445	174
Kinematic Viscosity @ 100°C (mm/s <sup>2</sup> )	ASTM D445	24.0
Pour Point (°C)	ASTM D97	-36
TBN		5.9
Viscosity Index	ASTM D2207	170

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturer's recommendations.
- This product, used in accordance with the manufacturer's recommendations, does not pose a health or safety risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60 °C, kept out of direct sunlight, protected from frost and



# AZTEC OILS

THE LUBRICATION SPECIALISTS



In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.