

## MOTOTEC TRANSFLUID

**Product Code:** MOT052 | **Revision:** 20240819



### Available Pack Sizes



### Applications

A premium synthetic transmission fluid for use in motorcycles and scooters which have a wet or dry clutch in a separate transmission case. Specially formulated using sophisticated additive technology to impart superb oxidation resistance, anti-wear characteristics and maintain durable frictional stability for effortless and smooth gear changes.

### Recommended by Aztec Oils as suitable for the following applications

Can be used in motorcycle, trials bike & scooter transmissions requiring a SAE 75W wet clutch compatible lubricant.

### Benefits

- Durable anti-shudder for consistent performance.
- Excellent foam control.
- Exceptional low temperature fluidity for improved lubrication during start-up & shiftability in cold climates.
- Good seal & material compatibility.
- Low viscosity helps reduce operational energy losses.
- Superior friction control allowing smooth gear changes.
- Superb oxidation & thermal stability.

### Typical Test Data

Appearance		Clear & bright, green
Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.84
Flash Point (°C)	ASTM D92	>180
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	33.4
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	7.0
Pour Point (°C)	ASTM D97	-45
Viscosity Index	ASTM D2207	178

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.