

MOTOTEC TRANS 85W

Product Code: MOT053 | **Revision:** 20250310



High performance semi synthetic transmission lubricant.

Available Pack Sizes



Applications

A high performance semi synthetic motorcycle and scooter transmission oil formulated using an advanced blend of base oils which have been carefully combined with specialised additive technology. Provides outstanding wear protection to transmission components under high loads and high engine speeds. Sophisticated friction modifiers enable a superb wet clutch response for smoother gear shifts and fast acceleration throughout the drain interval.

Recommended by Aztec Oils as suitable for the following applications

API GL-3
JASO MA, MA2
Suitable for scooter transmissions, including Vespa & Lambretta.

Benefits

- Exceptional anti-wear properties.
- Excellent oxidation & thermal stability.
- Good shear stability prevents viscosity break down.
- Shown to improve clutch life & reduce slippage.
- Provides protection to the transmission & wet clutches under the most demanding conditions.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.869
Flash Point (°C)	ASTM D92	220
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	112
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	14.3
Low Temperature Viscosity @ -26°C (cP)		27950
Pour Point (°C)	ASTM D97	<-30
Viscosity Index	ASTM D2207	129

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.