

MOTOTEC SCOOTER 4T 0W-30

Product Code: MOT054 | **Revision:** 20240819



Fully synthetic scooter engine oil, ACEA A5/B5

Available Pack Sizes



Applications

Fully synthetic four stroke engine oil specifically for scooters and maxi scooters. The robust formulation ensures excellent performance throughout frequent cold starts and high operating temperatures, making this ideal for models with injection engines, catalytic converters and particularly PIAGGIO i-Get engines.

Recommended by Aztec Oils as suitable for the following applications

ACEA A5/B5

Benefits

- Excellent low temperature performance.
- Improved performance & fuel efficiency.
- Long term anti-wear & oxidation stability.
- Outstanding protection against wear, rust & corrosion.
- PIAGGIO and Vespa scooters with i-Get engines requiring ACEA A5/B5, SAE 0W-30.
- Suitable for scooters with automatic start-stop systems.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.843
Flash Point (°C)	ASTM D92	210
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	53.5
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	10.0
Pour Point (°C)	ASTM D97	-40
Total Base Number (mg KOH/g)	ASTM D2896	10
Viscosity Index	ASTM D2207	177

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.