





MANUTEC MOULD RELEASE CM 45

Product Code: MOU015 | **Revision:** 20240821



Low viscosity oil based mould release agent.

Available Pack Sizes







Applications

Oil based mould release agent designed for most types of form work used in a variety of conditions. It utilises a specially selected release system to give optimum performance on both the mould life and surface finish of the components. For use in forming concrete fence posts, gravel and kicking boards. Also suitable for forming concrete T-beams.

Applications

This product should be applied to prepared moulds and formers by swab, brush or spray. On new wooden moulds two applications before first use will assist in extending the mould life.

Benefits

- · Can be used in various conditions.
- Optimum surface finish.
- Provides corrosion resistance to metal moulds.
- Suitable for a variety of different moulds.

Typical Test Data		
Appearance		Clear/straw fluid
Density @ 15°C (kg/m³)	ASTM D4052	0.82
Flash Point (°C)	ASTM D92	140
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	4.8

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- · When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.