


## MANUTEC MOULD RELEASE M 120

**Product Code:** MOU030 | **Revision:** 20240821



Hydrocarbon mould release agent.

### Available Pack Sizes



### Applications

A hydrocarbon based release fluid formulated principally for the production of moulded concrete products. Suitable for use on metal and timber form work, where it will preserve the timber and prevent corrosion on the metal. Produces a clean and positive release combined with a stain free finish.

### Applications

This product should be applied to prepared moulds and formers by swab, brush or spray. On new wooden moulds two applications before first use will assist in extending the mould life.

### Benefits

- Use on both metal and timber form work.
- Preserves timber moulds.
- Prevents metal corrosion.
- Produces blemish free products.
- Suitable for a variety of different moulds.

### Typical Test Data

|                                                 |                   |      |
|-------------------------------------------------|-------------------|------|
| Appearance                                      | Straw/amber fluid |      |
| Density @ 15°C (kg/m <sup>3</sup> )             | ASTM D4052        | 0.85 |
| Flash Point (°C)                                | ASTM D92          | >80  |
| Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s) | ASTM D445         | 12.0 |

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

- When disposing of the product after use, please protect the environment and comply with local regulations.
- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.