


## METALTEC MIRADRAW C 100

**Product Code:** NEAT031 | **Revision:** 20240821



A general-purpose chlorinated neat metal working fluid.

### Available Pack Sizes



### Applications

A neat forming/drawing oil blended from top quality solvent refined base oils together with special chlorinated and fatty esters additives to ensure high performance, better operator acceptability and enhanced extreme pressure performance. The use of non-staining additives provides a product ideal for use with non-ferrous metals.

### Recommended by Aztec Oils as suitable for the following applications

A versatile drawing/forming oil suitable for severe metal forming and drawing operations developed to provide virtually everything that today's modern press shop requires. An oil that is virtually odourless in operation.

### Benefits

- Does not stain non-ferrous metals.
- Exception tool life.
- Excellent results on a wide range of materials.
- Good surface finish.
- Low odour and misting for improved operator handleability.
- Outstanding boundary & EP lubrication.

### Typical Test Data

Appearance		Straw
Copper Corrosion (3h/100°C)	ASTM D130	1
Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.98
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	100

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using the product, it is advised to consult the Metal Working Fluids section of the Government HSE website.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.