


METALTEC MIRACUT C 20 FS

Product Code: NEAT071 | **Revision:** 20240821



A general-purpose chlorinated neat metal working fluid.

Available Pack Sizes



Applications

A high-performance neat cutting oil blended from top quality solvent refined base oils together with carefully selected chlorine, active sulphur and fatty additives to ensure excellent machining performance. The product is formulated with a medium viscosity to ensure better operator acceptability.

Recommended by Aztec Oils as suitable for the following applications

A versatile cutting oil developed to provide virtually everything that today's modern machine shop requires whether cutting, milling, thread cutting, tapping or just general machining of ferrous metals.

Benefits

- Exception tool life.
- Good surface finish.
- Low odour and misting for improved operator handleability.
- Suitable for heavy duty applications.
- Outstanding EP properties.

Typical Test Data

Appearance		Amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.88
Flash Point (°C)	ASTM D92	>150
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	24
Pour Point (°C)	ASTM D97	-18

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using the product, it is advised to consult the Metal Working Fluids section of the Government HSE website.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.