

## TOROTEC SS 10W-40

**Product Code:** PCM007 | **Revision:** 20250410



Semi synthetic automotive engine oil, ACEA A3/B4.

### Available Pack Sizes



### Applications

A multigrade engine oil manufactured from a precisely balanced blend of top-quality mineral and synthetic base stocks with performance enhancing technology. Formulated to have a high level of lubricity to provide lower internal friction for reduced engine wear whilst its relatively low viscosity improves flow rates and hydraulic tappet performance during cold start and engine idling.

Recommended by Aztec Oils as suitable for the following applications

ACEA A3/B3, A3/B4  
API SN/CF  
Mercedes-Benz 229.1/229.3  
Renault RN0700/RN0710  
VW 502.00/505.00

### Benefits

- Advanced anti-wear technology helps to protect engine components.
- Excellent protection against oxidation.
- High shear stability for stay in grade performance.
- Reduces corrosion, varnish and the agglomeration of sludge.
- Superb thermal stability at high temperatures.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.871
Flash Point (°C)	ASTM D92	220
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	95.5
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	13.8
Pour Point (°C)	ASTM D97	-32
Total Base Number (mg KOH/g)	ASTM D2896	10.3
Viscosity Index	ASTM D2207	147

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.



# AZTEC OILS

THE LUBRICATION SPECIALISTS



In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.