


TOROTEC 5W-30 DX

Product Code: PCM010 | **Revision:** 20240819



Fully synthetic & mid SAPS automotive engine oil, ACEA C3.

Available Pack Sizes



Applications

A fully synthetic and mid SAPS engine oil formulated for use with petrol and diesel engines, particularly developed for BMW, GM and Mercedes-Benz vehicles with exhaust after-treatment devices. Our specialist Adaptive Molecular Technology maintains engine power, maximises efficiency and improves reliability, ensuring optimum performance in all driving and stop-start conditions.

Recommended by Aztec Oils as suitable for the following applications

ACEA C3
API SN/CF
BMW LL-04
GM dexos2™
Mercedes-Benz 229.51/229.52
VW 505.01

Benefits

- Advanced anti-wear technology helps to protect engine components.
- Engineered to have good oxidation resistance and thermal stability.
- Excellent high and low temperature performance.
- High standards of engine cleanliness.
- Increased fuel efficiency.
- Maintains performance over extended service intervals.
- Robust detergency technology prevents the build-up of deposits to keep engines clean and prevent the agglomeration of sludge.

Typical Test Data

Density @ 15°C (kg/m³)	ASTM D4052	0.846
Flash Point (°C)	ASTM D92	212
Kinematic Viscosity @ 40°C (mm²/s)	ASTM D445	75
Kinematic Viscosity @ 100°C (mm²/s)	ASTM D445	12.2
Pour Point (°C)	ASTM D97	-45
Total Base Number (mg KOH/g)	ASTM D2896	7.8
Viscosity Index	ASTM D2207	160

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.