| | Applications A fully synthetic and mid SAPS engine oil formulated f | |
|--|---|--|
| Product Code: PCM019 Revision: 20240209 | use with petrol and diesel engines. Our specialist Adaptive Molecular Technology maintains engine power maximises efficiency and improves reliability whilst supporting exhaust after-treatment devices throughout the vehicle's lifecycle in mixed and stop-start driving conditions. Ideal for modern engines that require a hig level of protection in cold conditions. Previously called TOROTEC 0W-30 DX. Recommended by Aztec Oils as suitable for the following applications ACEA C3 BMW LL-04 Mercedes-Benz 229.52 Porsche C30 VW 504.00/507.00 | |
| Fully synthetic & mid SAPS automotive engine oil, ACEA C3. | Suitable for General Motors Benefits | |
| Available Pack Sizes | Advanced anti-wear technology helps to protect engine components. Compatible with diesel particulate filters (DPF) and three-way catalysts (TWC), including vehicles utilisi SCR technology. Engineered to have good oxidation resistance, therr stability and superb low temperature performance. High standards of engine cleanliness. Increased performance and fuel efficiency. Offers extended service intervals. | |
| | | |
| Typical Test Density @ 15°C (kg/m3) | Data ASTM D4052 0.843 | |
| Elech Deint (90) | | |

| Density @ 15°C (kg/m3) | ASTM D4052 | 0.843 |
|--|------------|-------|
| Flash Point (°C) | ASTM D92 | 212 |
| Kinematic Viscosity @ 100°C (mm/s ²) | ASTM D445 | 12.2 |
| Pour Point (°C) | ASTM D97 | -50 |
| Total Base Number (mg KOH/g) | ASTM D2896 | 7.4 |
| Viscosity Index | ASTM D2207 | 190 |

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.



THE LUBRICATION SPECIALISTS

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
 This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.