

TOROTEC 5W-20 FMC

Product Code: PCM030 | **Revision:** 20240909



Fully synthetic & low viscosity automotive engine oil.

Available Pack Sizes



Applications

A fully synthetic and fuel-efficient engine oil for use with modern petrol and diesel engines, particularly Ford vehicles. Our specialist Adaptive Molecular Technology maintains engine power, maximum efficiency and improves reliability, ensuring optimum performance whilst delivering outstanding durability in all driving conditions. Synergistically combined with advanced additive technology to provide exceptional resistance to thermal breakdown, outstanding low temperature performance and prevents the formation of harmful deposits.

Recommended by Aztec Oils as suitable for the following applications

API SN/CF
ILSAC GF-5
Ford WSS-M2C948-B

Benefits

- Excellent Low temperature performance.
- Improved performance and fuel efficiency.
- Long service intervals.
- Long term anti-wear and oxidation stability.
- Outstanding protection against wear, rust and corrosion.
- Suitable for Ford EcoBoost petrol engines.

Typical Test Data

Density @ 15°C (kg/m³)	ASTM D4052	0.845
Flash Point (°C)	ASTM D92	233
Kinematic Viscosity @ 40°C (mm²/s)	ASTM D445	45.1
Kinematic Viscosity @ 100°C (mm²/s)	ASTM D445	8.3
Pour Point (°C)	ASTM D97	-48
Total Base Number (mg KOH/g)	ASTM D2896	7.9
Viscosity Index	ASTM D2207	161

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.