

Applications

A fully synthetic and mid SAPS engine oil formulated for

TOROTEC OW-30 FMC

·	use with modern petrol and discel ongines, particular	
Product Code: PCM040 Revision: 20240819	 use with modern petrol and diesel engines, particularly Ford and Jaguar Land Rover vehicles. Our specialist Adaptive Molecular Technology maintains engine power, maximises efficiency and improves reliability whilst supporting exhaust after-treatment devices throughout the vehicle's lifecycle in mixed and stop-start driving conditions. Recommended by Aztec Oils as suitable for the following applications ACEA C2 Ford WSS-M2C950-A Jaguar Land Rover STJLR.03.5007 Suitable for Fiat 9.55535-DS1 Suitable for Fiat 9.55535-GS1 	
Fully synthetic, ACEA C2 automotive engine oil for Ford vehicles.	Suitable for BMW Benefits Compatible with diesel particulate filters (DPF) and	
Available Pack Sizes	 three-way catalysts (TWC), including those utilising SCR technology. Excellent engine cleanliness. Offers extended service intervals. Optimised fuel efficiency. Superior performance under both high and low temperature conditions. Supreme levels of engine protection. 	
Typical Test		
Density @ 15°C (kg/m ³)	ASTM D4052 0.843	
Flash Point (°C) Kinematic Viscosity @ 40°C (mm²/s)	ASTM D92 210 ASTM D445 53	
KINEINALIC VISCOSILV (W 40°C (IIIII14/S)	ASTR D443 53	

		01010
Flash Point (°C)	ASTM D92	210
Kinematic Viscosity @ 40°C (mm²/s)	ASTM D445	53
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	9.6
Pour Point (°C)	ASTM D97	-42
Total Base Number (mg KOH/g)	ASTM D2896	7.8
Viscosity Index	ASTM D2207	168

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.



THE LUBRICATION SPECIALISTS

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
 This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.
- Note: Not backwards compatible with older Ford specifications.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.